

TOPKRETE SEALCOAT 190

Topkrete Sealcoat 190 is a single component flexible waterproofing compound in powder form.

Description

Topkrete Sealcoat 190 is a single component flexible waterproofing coating. It consists of special modified polymer, modified cement, selected graded aggregates and special waterproofing additive.

Uses

- Protection of concrete structure
- Swimming pools
- Retaining wall and basement wall
- Bathroom or toilet
- Balcony
- Wet area

Advantage

- Flexible
- Easy to apply
- Crack bridging
- Single component
- Prevent water penetration
- Excellent adhesion to concrete
- Can be apply to damp substrate

Technical Data

Composition	Modified Cementitious-Polymer
Tensile Strength	≥ 1.0 N/mm ²
Crack Bridging	0.5mm
Appearance	Powder form
Color	Grey
Pot Life	~ 30 minutes
Water Penetration Resistant	Excelent

Application Instruction

The substrate shall be sound, free of oil, grease, dirt, laitance and other foreign material.

Blast cleaning, high pressure water jetting, wire brushing or grinding are recommenced to prepare the substrate to received Topkrete Sealcoat 190.

All the void, crack and honeycomb should be repair with Topkrete repair mortar.

Mixing

Topkrete Sealcoat 190 shall be mix in clean container using a low speed drill. Add Topkrete Sealcoat 190 into clean water slowly and mixed with a low speed drill with paddle until homogeneous mix and free of lumps is obtained.

Application

Applied Topkrete Sealcoat 190 by brush or roller evenly to the substrate and allow to dry and two coat is recommend to get the good performances.

Topkrete Sealcoat 190 can be applied by a steel trowel with even pressure to obtained a uniform thickness

Coverage

2kg/m² is recommended.

Cleaning

Tools and equipment can be clean with water after used.

Shelf Life

6 months from the date of production under proper covered dry condition. Protect from direct sunlight and rain and water.

Packaging

25kg per bag

Technical Support

TOPKRETE offers a comprehensive range of high performance, quality products. TOPKRETE offers a technical support package to specifiers and contractors which include assistance with product selection and technical advice from staff with unrivalled experience in the industry.

Health & Safety

For further information, refer to the product Material Safety Data Sheet, available upon request.

Additional Information

Topkrete manufacturers and offers a wide range of complementary products which includes waterstop, waterproofing products, grouts, anchors, specialized flooring products. In addition, a wide range of products formulated for repair and refurbishment of spelled concrete are available.

Warranty

Topkrete Sdn Bhd warrants that the products manufactured by it shall be free from material defects and will conform to formulation standards and contain all components in their proper proportion. Should any of the products be proven defective, the liability to TOPKRETE SDN BHD shall be limited to replacement of the material proven to be defective, and TOPKRETE SDN BHD shall in no case be liable otherwise or for incidental or consequential damages. TOPKRETE SDN BHD MAKES NO WARRANTY AS TO MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES EXPRESSED OR IMPLIED. User shall determine the suitability of the product for its intended use and assume all risks and liability in connection therewith.

Important note

Topkrete products are guaranteed against defective materials and manufacture and are sold subject to its standard Terms and Conditions of Sale, copies of which may be obtained on request. Whilst Topkrete endeavors to ensure that any advice, recommendation, specification or information it may give is accurate and correct, it shall not, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products, whether or not in accordance with any advice, specification, recommendation or information given by it.

Topkrete Sdn Bhd (597943-M)

Office : 19-G, Blok A, Jalan Atmosphere 3,
Pusat Perniagaan Atmosphere,
Bandar Putra Permai,
43300 Seri Kembangan,
Selangor Darul Ehsan. Malaysia
Tel: +603- 8957 8999 Fax: +603-8959 1661
Email: info@topkrete.com
www.topkrete.com

Factory : No.3, Jalan Utama 1/12,
Taman Perindustrian Puchong Utama,
47100 Puchong,
Selangor Darul Ehsan. Malaysia.
Tel : +603-80631883 Fax: +603-80631983