

# TOPSEAL ACI PRIMER

A two component, high performance epoxy anti-rust primer based on zinc phosphate specially formulated for excellent corrosion resistance.

## Description

This is high performance anti-rust primer for protection of steel. It protects the iron products and facilitates the adhesion of the finishing product. It is fast drying and has good corrosion inhibiting properties.

## Uses

Topseal ACI Primer is ideal for architectural and light commercial construction, and is ideal for application on steel to protect against atmospheric exposure.

## Characteristic

- Easy to use
- Fast drying

## Substrate Preparation

To secure lasting adhesion to the subsequent product, all surfaces shall be clean, dry and free from any contamination. The correct surface preparation of the substrate will guarantee the best results in term of product yield, appearance and resistance in time of the finish.

## Properties

Physical Properties	Result
Volume Solids	>55%
Mix Ratio	4.2 Base : 0.8 Hardener
Drying Time (25°C)	1 hour
Pot Life	30mins
Colour Range	White, Grey

## Application

Installation should be carried by experienced and profession applicator.

## Cleaning

Tools should be cleaned with solvents immediately after use.

## Health & Safety

For further information, refer to the product Material Safety Data Sheet, available upon request.

## Technical Support

TOPKRETE offers a comprehensive range of high performance, quality products. TOPKRETE offers a technical support package to specifiers and contractors which include assistance with product selection and technical advice from staff with unrivalled experience in the industry.

## Warranty

Topkrete Sdn Bhd warrants that the products manufactured by it shall be free from material defects and will conform to formulation standards and contain all components in their proper proportion. Should any of the products be proven defective, the liability to TOPKRETE SDN BHD shall be limited to replacement of the material proven to be defective, and TOPKRETE SDN BHD shall in no case be liable otherwise or for incidental or consequential damages. **TOPKRETE SDN BHD MAKES NO WARRANTY AS TO MERCHANTABILITY OR FITNESS FOR A PARTICULAR PURPOSE AND THIS WARRANTY IS IN LIEU OF ALL OTHER WARRANTIES EXPRESSED OR IMPLIED.** User shall determine the suitability of the product for its intended use and assume all risks and liability in connection therewith.

## Important note

Topkrete products are guaranteed against defective materials and manufacture and are sold subject to its standard Terms and Conditions of Sale, copies of which may be obtained on request. Whilst Topkrete endeavors to ensure that any advice, recommendation, specification or information it may give is accurate and correct, it shall not, because it has no direct or continuous control over where or how its products are applied, accept any liability either directly or indirectly arising from the use of its products, whether or not in accordance with any advice, specification, recommendation or information given by it.

## Topkrete Sdn Bhd (597943-M)

Office: 19-G, Blok A, Jalan Atmosphere 3,  
Pusat Perniagaan Atmosphere,  
Bandar Putra Permai,  
43300 Seri Kembangan,  
Selangor Darul Ehsan. Malaysia  
Tel: +603- 8957 8999  
Fax: +603-8959 1661  
Email: info@topkrete.com  
www.topkrete.com

Factory: No.3, Jalan Utama 1/12,  
Taman Perindustrian Puchong Utama,  
47100 Puchong,  
Selangor Darul Ehsan. Malaysia.  
Tel: +603-80631883 Fax: +603-80631983